

Network Systems ► Wall-mounted Distributer ► Wall-mounted Distributer ODB/5



General Information

The ODB/5 is a small and compact wall-mounted distributor for indoor and outdoor application. It can hold up to 12 ports and up to 12 splices in a hinged cassette.

Moreover it is possible to accommodate power splitters and wavelength division multiplexers for WWDM-, CWDM- or DWDM-solutions for FTTH. The modular design allows an easy and quick installation. An optional lock prevents any unauthorized access.

Features

- Wall-mounted distributor for indoor/outdoor application
- Robust enclosure consisting of chassis and hinged cover (optional with lock)
- Adapter plate for up to 6 ports of the type LSH (Class A) and SC (Class A) or 12 ports of the type LC (Class A)
- Splice storage system with additional cover for up to 12 splices or up to 6 couplers/filters
- Patch and OSP cable routing via separable rubber gaskets (or optional metric glands)

- Separate cable entries for cables with max. outer diameter of 10 mm (standard) or 14 mm (option)
- Integration of a gas stopper is possible
- Available also with installed lead-in connectors and pigtails, ready for splicing (on request)

Dimensions

- 235 × 156 × 45 mm

Weight

- 0.5 kg

Material

- PC / ABS

Colour

- RAL 7035

IP Rating

- IP 54

Dimensions

